



Numonics Corporation
 101 Commerce Drive • PO Box 1005
 Montgomeryville, PA 18936 • USA
 Tel: 215-362-2766 • Toll Free: 800-523-6716
 Fax: 215-361-0167
 Email: numonics@numonics.com
 URL: www.numonics.com



AccuGrid includes all major emulations.
 It's the most sophisticated advancement in digitizing tablet technology, incorporating all major emulations: Numonics, Calcomp, Summagraphics and GTCO.

We're there for you.
 Numonics is more than a manufacturer of digitizers. We solve unique input device and imaging problems for OEM's and systems integrators. So think of us as your technology partner. And count on us to assist you in the development of cost-effective and creative solutions that make integration easier.

Easy to set up. Easy to use. Easy to like!
 AccuGrid's streamlined contemporary design makes everything look simple. And it is! Tablet set-up is done with a user-friendly menu – there are no dip switches to set and reset. On-tablet soft keys make switching between user-defined configurations as easy as one key press. And you have your choice of transducers, 4-button cursor or 16-button cursor. It's fast. Efficient. Accurate. Designed to work the way you do.

The high performance tablet with the low profile.
 AccuGrid's thin profile contains a wide range of impressive features including:

- An easy, user-friendly set-up menu
- On-tablet softkeys for easy configuration switching
- Resolution 1000 lpi
- Drivers for Win 9X /Me / NT / 2000 / XP Operating Systems and multipointing mode, allowing mouse/cursor and tablet to work together

AccuGrid IV Opaque Standard Accuracy Specifications

Accuracy: ± 0.010" (0.254mm)
 Interface: RS232 9-pin D-type or USB

Pointing Devices

- 4-button corded cursor
- 4-button cordless cursor
- 16-button corded cursor
- 16-button cordless cursor

Model	Active Area	Actual Footprint	Weight
AF56	20" x 24" 50cm x 60cm	26-1/4" x 30-1/8" 66.7cm x 76.5cm	9 lbs. (4.1 kg)
AF60	24" x 36" 60cm x 90cm	30-1/8" x 42" 76.5cm x 106.7cm	17 lbs. (7.7 kg)
AF90	36" x 48" 90cm x 120cm	42" x 53-7/8" 106.7cm x 136.8cm	23 lbs. (10.5 kg)
AF110	44" x 60" 110cm x 150cm	49-1/8" x 66-7/8" 124.8cm x 169.9cm	31 lbs. (14.1 kg)

A Limited Lifetime Warranty.

The AccuGrid digitizer carries a limited lifetime warranty against manufacturing defects. The accessories shipped with the AccuGrid, such as the 4- and 16-button cursors, are under warranty for two years from the date of purchase.



All Models Menu Selectable Emulations & Options Emulations:

- Numonics – binary & ASCII
- GTCO – hi-res & lo-res binary & ASCII
- CalComp – binary & ASCII
- Summagraphics – binary & ASCII

Baud Rates: 1200 to 19,200

Modes: Stream, Switched Stream, Point & Polled

Resolution: 1000 lpi, settable up to 100 lpmm (2540 lpi)

Input voltage: 110V to 240V

Operating Temperature: 50°F to 104°F (10°C to 40°C)

Storage Temperature: 14°F to 131°F (-10°C to 55°C)

Humidity: 90% (non-condensing)

Safety Approvals:

- UL 1950
- CAN/CSA C22.2 No. 950
- EN 60950